


B15 RATED WALL SYSTEM for wet areas

Snap connection with bottom straight slot

TYPE B-13-052



GENERAL INFORMATIONS:

Fire class: B15

Standard panel width (B): 300, 450, 580 mm

Panel width (possible options) :


- 150-580 mm* (B15 certified)
- up to 1000 mm* (non- certified)

Standard panel height (H):


- up to 2600 mm* (B15 certified)
- up to 3000 mm* (non- certified)

Mass: 25mm – 15,2 kg/ m²

CROSS-SECTION:




JOINING METHOD:



PRODUCT CODE EXAMPLE:

B-13-052	- B15	- 25	- 580x2000	- Galv	- 9010	- Galv
TYPE	FIRE RATE	THICKNESS	SIZE BxH	MATERIAL	1. FINISH	2. FINISH

BOTTOM SIDE:



MATERIAL:

1. Galvanized steel 0,6 mm (Stainless steel 0,6 mm)
2. Mineral wool density 175 kg/m³
3. Galvanized steel 0,6 mm (Stainless steel 0,6 mm)
4. Profile - Galvanized steel 1,0 mm (Stainless steel 1,0 mm)

FINISHING:

- RAL
- PVC Foil
- Galvanized steel
- Stainless steel

*For more information, contact us.